



FLOOD LIGHT

FEATURE特点

Die-cast Aluminum
High thermal conductivity
HC SEMITEK LED
Yimingyuan Driver, Efficiency >90%
3 years warranty
Long life time 50,000 hours
Impact test IK08
Waterproof IP66
Electrical: 85V-265V, 50/60HZ
CRI>70
Surge protection 4KV

APPLICATION SCENARIOS应用场景

Garden, School, Square, Yard, RESidential community, Road



SAFETY FEATURES安全特点



PRODUCT PARAMETERS产品参数

Model	Watt (W)	Voltage (V)	Lumen (lm)	CRI	Power factor	Beam Angle	IP	LED	Driver	LxWxH (mm)
YMY-0902W-050	50	85-265	6000	>70	0.95	120°	IP66	HC SEMITEK	YIMINGYUAN	185*85*65
YMY-0902W-100	100	85-265	12000	>70	0.95	120°	IP66	HC SEMITEK	YIMINGYUAN	275*185*70
YMY-0902W-150	150	85-265	18000	>70	0.95	120°	IP66	HC SEMITEK	YIMINGYUAN	385*265*70
YMY-0902W-200	200	85-265	24000	>70	0.95	120°	IP66	HC SEMITEK	YIMINGYUAN	385*265*70
YMY-0902W-300	300	85-265	36000	>70	0.95	120°	IP66	HC SEMITEK	YIMINGYUAN	415*340*72
YMY-0902W-400	400	85-265	48000	>70	0.95	120°	IP66	HC SEMITEK	YIMINGYUAN	515*336*72

